


CANDELA

LED A FILAMENTO



COD. CODE	ATTACCO BASE TYPE	WATT POWER INPUT	EQ. INC.	°K	LUMEN (Lm)	ANGOLO ANGLE	ILL. ACC ACCENT LIGHT	DIMENSIONI DIMENSIONS MM	EAN	FATTORE P. POWER FACTOR	AVVIO AL 60% WARM UP 60%	
22450	E14	4 W	35	3000°K	420	330°	NO	35X99	8027940155968	≥ 0,40	1,0 s	6/36

RESACROM. REND. INDEX (Ra)	MERCURIO MERCURY	ACCENSIONI ON / OFF	TENSIONE V/Hz Voltage	CLASS. EN.	SOPRAV. 6000 h SURVIVAL 6000 h	INNESCO STARTING	FATT. LUM FINE VITA LLMF END LIFE	UNIFORMITA COLORE COLOR CONSISTENCY	GUASTI PREM. 1000h PREM. FAILURE 1000h	VITA LIFE TIME
≥ 80	≤ 0 mg	≥ 15.000	220-240V 50-60 Hz	A+	≥ 0,9	< 0,5 s	≥ 0.7	< 6 SDCM	≤ 5%	30.000

LED A FILAMENTO



MINI GLOBO GOCCIA

LED A FILAMENTO

LED A FILAMENTO



COD CODE	ATTACCO BASE TYPE	WATT POWER INPUT	EQ. INC.	°K	LUMEN (Lm)	ANGOLO ANGLE	ILL. ACC ACCENT LIGHT	DIMENSIONI DIMENSIONS MM	EAN	FATTORE P. POWER FACTOR	AVVIO AL 60% WARM UP 60%	
22460	E14	4 W	35	3000°K	420	330°	NO	45X78	8027940155975	≥ 0,40	1,0 s	6/36
22470	E27	4 W	35	3000°K	420	330°	NO	45X72	8027940155982	≥ 0,40	1,0 s	6/36

COD CODE	ATTACCO BASE TYPE	WATT POWER INPUT	EQ. INC.	°K	LUMEN (Lm)	ANGOLO ANGLE	ILL. ACC ACCENT LIGHT	DIMENSIONI DIMENSIONS MM	EAN	FATTORE P. POWER FACTOR	AVVIO AL 60% WARM UP 60%	
22480	E27	6 W	50	3000°K	630	330°	NO	60X105	8027940155999	≥ 0,50	1,0 s	6/36
22490	E27	8 W	60	3000°K	810	330°	NO	60X105	8027940156002	≥ 0,50	1,0 s	6/36

RESACROM. REND. INDEX (Ra)	MERCURIO MERCURY	ACCENSIONI ON / OFF	TENSIONE V/Hz Voltage	CLASS. EN.	SOPRAVV. 6000 h SURVIVAL 6000 h	INNESCO STARTING	FATT.LUM FINE VITA LLMF END LIFE	UNIFORMITA COLORE COLOR CONSISTENCY	GUASTI PREM.1000h PREM.FAILURE 1000h	VITA LIFE TIME
≥ 80	≤ 0 mg	≥ 15.000	220-240V 50-60 Hz	A+	≥ 0,9	< 0,5 s	≥ 0.7	< 6 SDCM	≤ 5%	30.000

RESACROM. REND. INDEX (Ra)	MERCURIO MERCURY	ACCENSIONI ON / OFF	TENSIONE V/Hz Voltage	CLASS. EN.	SOPRAVV. 6000 h SURVIVAL 6000 h	INNESCO STARTING	FATT.LUM FINE VITA LLMF END LIFE	UNIFORMITA COLORE COLOR CONSISTENCY	GUASTI PREM.1000h PREM.FAILURE 1000h	VITA LIFE TIME
≥ 80	≤ 0 mg	≥ 15.000	220-240V 50-60 Hz	A+	≥ 0,9	< 0,5 s	≥ 0.7	< 6 SDCM	≤ 5%	30.000




GLOBO

FILAMENTO LED

LED A FILAMENTO



COD CODE	ATTACCO BASE TYPE	WATT POWER INPUT	EQ. INC.	°K	LUMEN (Lm)	ANGOLO ANGLE	ILL. ACC ACCENT LIGHT	DIMENSIONI DIMENSIONS MM	EAN	FATTORE P. POWER FACTOR	AVVIO AL 60% WARM UP 60%	
22500	E27	8 W	60	3000°K	810	330°	NO	125X165	8027940156019	≥ 0,50	1,0 s	6/36

RESACROM. REND.INDEX (Ra)	MERCURIO MERCURY	ACCENSIONI ON / OFF	TENSIONE V/Hz Voltage	CLASS. EN.	SOPRAV. 6000 h SURVIVAL 6000 h	INNESCO STARTING	FATT.LUM FINE VITA LLMF END LIFE	UNIFORMITA COLORE COLOR CONSISTENCY	GUASTI PREM.1000h PREM.FAILURE 1000h	VITA LIFE TIME
≥ 80	≤ 0 mg	≥ 15.000	220-240V 50-60 Hz	A+	≥ 0,9	< 0,5 s	≥ 0.7	< 6 SDCM	≤ 5%	30.000

