




PROIETTORI LED

# PROIETTORI LED

PROIETTORI LED



COD CODE	WATT POWER INPUT	EQ. INC.	°K	LUMEN (Lm)	ANGO-LO ANGLE	ILL. ACC ACCENT LIGHT	DIMENSIONI DIMENSIONS MM	GRADO IP IP GRADE	CAVO WIRE	EAN	FATTORE P. POWER FACTOR	AVVIO AL 60% WARM UP 60%	
22510	10 W	60 W	4000°K	870	100°	NO	130x110x35	IP65	35cm	8027940156040	≥ 0,5	1,0 s	1/24
22515	20 W	110 W	4000°K	1740	100°	NO	186x157x47	IP65	35cm	8027940156057	≥ 0,5	1,0 s	1/20
22520	30 W	150 W	4000°K	2610	100°	NO	230x195x51	IP65	35cm	8027940156064	≥ 0,9	1,0 s	1/16
22525	50 W	250 W	4000°K	4350	100°	NO	286x241x62	IP65	35cm	8027940156071	≥ 0,9	1,0 s	1/8

RESACROM. REND. INDEX (Ra)	MERCURIO MERCURY	ACCENSIONI ON / OFF	TENSIONE V/Hz Voltage	CLASS. EN.	SOPRAVV. 6000 h SURVIVAL 6000 h	INNESCO STARTING	FATT.LUM FINE VITA LLMF END LIFE	UNIFORMITA COLORE COLOR CONSISTENCY	GUASTI PREM.1000h PREM.FAILURE 1000h	VITA LIFE TIME
≥ 80	≤ 0 mg	≥ 15.000	220-240V 50-60 Hz	A+	≥ 0,9	< 0,5 s	≥ 0.7	< 6 SDCM	≤ 5%	30.000

