


# G4



G4 1,5W  
SILICONE



G4 3W  
CERAMICA

COD. CODE	ATTACCO BASE TYPE	WATT POWER INPUT	EQ. INC.	°K	LUMEN (Lm)	ANGOLO ANGLE	ILL. ACC ACCENT LIGHT	DIMENSIONI DIMENSIONS MM	EAN	FATTORE P. POWER FACTOR	AVVIO AL 60% WARM UP 60%	
22300	G4	1,5 W	10	3000°K	110	360°	NO	10X35	8027940155388	≥ 0,40	1,0 s	10/100
22305	G4	3 W	28	3000°K	300	360°	NO	16X43	8027940155395	≥ 0,40	1,0 s	10/100

RESACROM. REND. INDEX (Ra)	MERCURIO MERCURY	ACCENSIONI ON / OFF	TENSIONE V/Hz Voltage	CLASS. EN.	SOPRAW. 6000 h SURVIVAL 6000 h	INNESCO STARTING	FATT.LUM FINE VITA LLMF END LIFE	UNIFORMITA COLORE COLOR CONSISTENCY	GUASTI PREM.1000h PREM.FAILURE 1000h	VITA LIFE TIME
≥ 80	≤ 0 mg	≥ 7.500	12V 50-60 Hz	A++	≥ 0,9	< 0,5 s	≥ 0.7	< 6 SDCM	≤ 5%	15.000